

Capacity	120 Pole over 5 x Din rails of 24	
Finished Dimensions	Height	980mm
	Width	590mm
	Recessed Depth	90mm
	Recessed Width	605mm
	Recessed Height	1010mm
Mounting	Flush as Standard – 10-16mm Wall lining thickness	
Locking	Non locking – push catch	
Door Swing	LH Hinged, can be field reversed.	
Construction Material	1.0mm Mild Steel	
Mechanical Protection	2.0mm Steel Plate that can be fitted top or bottom next to cables entries.	
Included Accessories	5 x 6 Pole, Pole Filler Strip 18 x 38mm Snap Bushes circuit indication stickers	
Earth & Neutral Bars	42Pole + 2 Main Tunnels up to 16mm ²	
Finish / Colour	Primed in white ready for painting	
Installation Location	Indoor	
IP Rating	N/A	
Cable Entry	9 x 38mm Knockouts to top – 9 x 38mm knockouts to bottom	
Compliance and Standards	AS/NZS IEC 60670.1:2012	
	AS/NZS3000:2018	
MIN / MAX Temp	-5 Degrees - +60 Degrees	
Max Current	100 Amp	
Rated Voltage	230V/415V AC 50Hz	
Weight	TBC	
Shipping Information		
Packaging	Outer cardboard packing, 1200mmx740mmx110mm	
Warranty	24 Month Standard Built Boards Warranty	